

STOTHERM POLYSTYRENE CONSTRUCTION SYSTEM

SS105 STOTHERM VARIO PLASTER SYSTEM BRANZ APPRAISAL CERTIFICATE NO. 478 INCORPORATING:

- STOLEVELL or MULTISCREED UNI MESH BASE PLASTER 25kg BAG EUROPEAN FIBRE REINFORCED CEMENT BASED WHITE PLASTER USED WITH EUROPEAN MESH AS A REINFORCING BASE PLASTER
- 2. STOPLEX W SEALER 10It CONTAINER EUROPEANACYLIC/SILANE PRIMER TO SEAL MINERAL SURFACES
- 3. STOLIT K COLOURED 25kg PAIL EUROPEAN FIBRE REINFORCED NON CEMENT COLOURED FINISHING RENDER AVAILABLE IN 1.0/1.5/2.0/3.0mm SIZED TEXTURE IN A PAIL
- 4. STOCOLOR

: MAXICRYL MATT FACADE PAINT 15It PAIL

: LASTIC SATIN FACADE PAINT 15It PAIL : LOTUSAN MINERAL RESIN PAINT 15It PAIL

SS106 STOTHERM CLASSIC PLASTER SYSTEM BRANZ APPRAISAL CERTIFICATE NO. 478 INCORPORATING:

- MULTISCREED PLASTER 25kg BAG BASECOAT PLASTER TO STRAIGHTEN AND PROVIDE A SOLID THICKER BASECOAT
- 2. STOARMAT CLASSIC PLASTER 23kg PAIL EUROPEAN FIBRE REINFORCED NON CEMENT BASED CRACKED RESISTANT PLASTER USED WITH EUROPEAN MESH AS A REINFORCEMENT PLASTER
- 3. STOLIT K or MP COLOURED RENDER 25kg PAIL EUROPEAN FIBRE REINFORCED NON CEMENT COLOURED FINISHING RENDER AVAILABLE IN 1.0/1.5/2.0/3.0mm SIZED TEXTURE AND MP or MP NATURAL SPONGE FINISHED RENDER
- 4. STOCOLOR : MAXICRYL MATT FACADE PAINT 15It PAIL
 - : LASTIC SATIN FACADE PAINT 15It PAIL
 - : LOTUSAN MINERAL RESIN PAINT 15It PAIL

STOTHERM SYSTEM

STOTHERM CONSTRUCTION SYSTEM INTRODUCTION

ST 006

2014

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.