



- WALL FRAMING
- WALL UNDERLAY
- STOTHERM 20mm VH CAVITY BATTEN
- OVERLAY OF STOFLEXYL MEMBRANE UNDER MESH COAT TO TOP & SIDES 75mm MIN. DOWNTURN OVER BASE COAT PLASTER
- STOTHERM CAP AT 10° OVERSEATS WALLS, GLUE TO 9mm FIBRE CEMENT SHEET OR H3.1 PLYWOOD OVER TOP PLATE/CAVITY
- 9mm FIBRE CEMENT SHEET OR H3.1 PLYWOOD OVER FRAMING
- STOTHERM 20mm VH CAVITY BATTEN

NOTE:
 APPLY STOFLEXYL MESHED WATERPROOFING OVER LEVELITE BASECOAT
 STOFLEXYL MESHED WATERPROOFING HAS BEEN TESTED BY **BRANZ** TO MEET THE REQUIREMENTS OF **AS/NZS4858** FOR A WATERPROOFING MEMBRANE AS REQUIRED BY **E2/AS1**

SCALE 1:5

STOTHERM SYSTEM	STOTHERM CONSTRUCTION SYSTEM	ST 505
	STOFLEXYL MESHED SADDLE FLASHING - ISOMETRIC	2014

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.