



STOTHERM MASONRY  
INSULATION PLASTER SYSTEM  
OVER STOTHERM INSULATION  
PANEL

APPLY TWO (2) COATS OF STO  
FLEXYL WATERPROOFING TO  
ALL REBATES

STO PREMESHED DRIP EDGE  
SEALANT OVER BOND  
BREAKER CONTINUOUS  
ACROSS HEAD & JAMB

SELECTED  
CONC.BLOCK  
AIR SEAL OVER  
BACKING ROD

TIMBER DOOR  
JOINERY PROFILES  
AS PER NZS 3610

\* REBATE TO SUIT  
SILL PROFILE  
LINE OF CONCRETE  
BLOCK & FOUNDATION  
- SHOWN DASHED

APPLY TWO COATS OF STO  
FLEXYL WATERPROOFING TO  
ALL REBATES OVER BASECOAT  
50mm MIN.DOWN WALL

SCALE 1:5

<b>STO CONCRETE BLOCK</b>	<b>STO CONCRETE BLOCK INSULATION SYSTEM TIMBER DOOR JOINERY - HEAD &amp; SILL DETAIL</b>	<b>STCB 405</b>
		<b>2014</b>

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.