



FIBRE CEMENT SHEET TO OVERHANG VERMIN TRAY BY 15mm min. FIT CLIPON TRAY AND LEAVE 5mm min. CLEARANCE TO HEAD FLASHING.
 PROPRIETARY ALUM. HEAD FLASHING TO COVER WINDOW FACING BY 20mm SLOPED 15° WITH min. 35mm UPSTAND TAPED TO WALL UNDERLAY
 ALLOW HEAD FLASHING TO PASS JAMBS BY 30mm BEND UP ENDS BY 20mm TO CREATE STOP ENDS IN CAVITY
 FLASHING TAPE SYSTEM TO BE INSTALLED AROUND JOINERY OPENINGS AS PER E2/AS1 BY BUILDER.

SCALE 1:2

<p>STO/ MONOTEK</p>	<p>STOARMAT CONSTRUCTION SYSTEM TIMBER WINDOW JOINERY - HEAD DETAIL</p>	<p>MFCS 870 2014</p>
--------------------------------	--	---------------------------------

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.