



**NOTE:**

- **E2AS1** REQUIRES BALCONIES AND PARAPET WALLS TO BE OFFSET FROM MAIN WALL PLANE TO ALLOW FOR SADDLE FLASHINGS.
- MESHED STOFLEXYL WATERPROOFING HAS BEEN TESTED BY **BRANZ** TO MEET **AS/NZS 4858** AS REQUIRED BY **E2/AS1**
- ALL WALL CAPS (MIN. 10° FALL) SHALL HAVE STOFLEXYL WATERPROOFING AS SHOWN OVER THE BASECOAT RENDER.

SCALE 1:5

|                       |   |               |
|-----------------------|---|---------------|
| <b>STOLITE SYSTEM</b> | <b>STOLITE CONSTRUCTION SYSTEM</b>                | <b>SL 505</b> |
|                       | <b>MESHED STOFLEXYL WATERPROOFING - ISOMETRIC</b> | <b>2022</b>   |

The information contained on this page is based on our experience and research at the date of issue. The detail is for use by Registered Architects, Licensed Designers or Chartered Engineers to assist in developing project details using Sto Systems. Stoanz Ltd reserve the right to alter or update information at any time without prior notice and it is the responsibility of the designer, project manager or Sto contractor to ensure they have and use the current Sto details and specifications on site.