



AIRSEAL OVER PEF ROD

- STOLITE RENDER SYSTEM
- 6mm MIN. FIBRE CEMENT SHEET
- 20mm DRAINED AND VENTED CAVITY
- WALL UNDERLAY
- FLASHING TAPE ONTO WALL UNDERLAY AND OVERLAPPING HEAD FLASHING
- VENTED VERMIN TRAY
- STOLITE CLIP-ON FOOT TRAY
- MIN. 5mm GAP REQUIRED
- ALUMINIUM WINDOW HEAD FLASHING, SUPPLIED AND INSTALLED BY MAIN CONTRACTOR, MIN. 15° SLOPE AND 10mm COVER AT WINDOW HEAD
- SEALANT REQUIRED FOR VERY HIGH AND EXTRA HIGH WIND ZONES
- PROPRIETARY HOMERIT PVC WINDOW JOINERY

1. IN EXTRA HIGH WIND ZONES INCREASE FLASHING COVER TO 60mm AND USE A RIGID UNDERLAY

SCALE 1:2

STOLITE SYSTEM	STOLITE CONSTRUCTION SYSTEM	SL 877
	HOMERIT PVC JOINERY - HEAD DETAIL	2022

The information contained on this page is based on our experience and research at the date of issue. The detail is for use by Registered Architects, Licensed Designers or Chartered Engineers to assist in developing project details using Sto Systems. Stoanz Ltd reserve the right to alter or update information at any time without prior notice and it is the responsibility of the designer, project manager or Sto contractor to ensure they have and use the current Sto details and specifications on site.